the first the two tests and the test the test the test that the test that





FIG. 1B



the feet of the fe

FIG. 2




FIG. 3







FIG. 4






CLOCK: EXCLUSIVE-OR SIGNAL BETWEEN DATA AND STROBE

FIG. 6



.

FIG. 7



. . .





FIG. 9



BRANCH: NODE WITH TWO OR MORE NODE CONNECTIONS


LEAF: NODE WITH SINGLE PORT CONNECTION


: PORT

c : PORT CORRESPONDING TO CHILD NODE p : PORT CORRESPONDING TO PARENT NODE

FIG. 10A

FIG. 10B





AND AND AND AND AND AND

13

IJ

ŀŁ






FIG. 13





ISO GAP: ISOCHRONOUS GAP

FIG. 15A




FIG. 15B

| 110145 | • |
|-------------------------------------|---|
| NAME | CONTENT |
| destination identifier | ID OF DESTINATION NODE (ASYNCHRONOUS ONLY) |
| transaction label | LABEL INDICATING A SERIES OF TRANSACTIONS (ASYNCHRONOUS ONLY) |
| retry code | CODE INDICATING RETRANSMISSION STATUS (ASYNCHRONOUS ONLY) |
| transaction code | CODE INDICATING PACKET TYPE (ASYNCHRONOUS ONLY) |
| priority | PRIORITY ORDER (ASYNCHRONOUS ONLY) |
| source identifier | SOURCE NODE (ASYNCHRONOUS ONLY) |
| destination memory address | MEMORY ADDRESS OF DESTINATION NODE (ASYNCHRONOUS ONLY) |
| response code | RESPONSE STATUS (ASYNCHRONOUS ONLY) |
| quadiet(4bytes) data | 4-BYTE LENGTH DATA (ASYNCHRONOUS ONLY) |
| length of data | LENGTH OF data_field (EXCEPT pad bytes) |
| extended transaction code | EXTENDED TRANSACTION CODE (ASYNCHRONOUS ONLY) |
| isochronous identifier | IDENTIFICATION OF ISOCHRONOUS PACKET |
| synchronization code | SYNCHRONIZATION OF VIDEO IMAGE AND AUDIO INFORMATION |
| contents of the CYCLE_TIME register | CYCLE TIMER REGISTER VALUE OF CYCLE MASTER NODE (CYCLE PACKET ONLY) |
| data + pad bytes | DATA STORAGE (ISOCHRONOUS AND ASYNCHRONOUS) |
| CRC for header field | CRC FOR HEADER |
| CRC for data field | CRC FOR DATA |
| tag label | ISOCHRONOUS PACKET FORMAT |
| | transaction label retry code transaction code priority source identifier destination memory address response code quadiet(4bytes) data length of data extended transaction code isochronous identifier synchronization code contents of the CYCLE_TIME register data + pad bytes CRC for header field CRC for data field |

FIG." 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20









FIG. 22






ا المستريخ المستريخ

FIG. 24





the fact that the three first from the training and the first firs

FIG. 26A CSR CORE REGISTER

| OFFSEI (hexadecimal) | REGISTER NAME | FUNCTION |
|-------------------------|---|---|
| | STATE_CLEAR | INFORMATION ON STATUS AND CONTROL |
| | STATE_SET | INFORMATION ON WRITE ENABLE/DISABLE STATUS OF STATE_CLEAR |
| | NODE_IDS | BUS ID + NODE ID |
| | RESET_START | TO RESET BUS BY WRITING INTO THIS AREA |
| 01ŷ~014 | INDIRECT_ADDRESS, INDIRECT_DATA | REGISTER TO ACCESS ROM AREA GREATER THAN 1KB |
| 018~01C | SPLIT_TIMEOUT | TIMER VALUE TO DETECT TIME-OU! OF SPLIT TRANSACTION |
| 020~02C | ARGUMENT, TEST_START, TEST_STATUS | REGISTER FOR DIAGNOSIS |
| 030-04C | UNITS_BASE, UNITS_BOUND, MEMORY_BASE, MEMORY_BOUND | NOT INSTALLED IN IEEE 1394 |
| 050~054 | INTERRUPT_TARGET, INTERRUPT_MASK | REGISTER OF INTERRUPTION NOTIFICATION |
| 058~07C | CLOCK_VALUE, CLOCK_TICK_PERIOD, CLOCK_STOROBE_ARRIVED, CLOCK_INFO | NOT INSTALLED IN IEEE 1394 |
| 080~0FC | MESSAGE_REQUEST, MESSAGE_RESPONSE | REGISTER FOR MESSAGE NOTIFICATION |
| 100~17C | | RESERVATION |
| 180~1FC | ERROR_LOG_BUFFER | TO RESERVE FOR IEEE 1394 |
| | | |

FIG. 26B SERIAL BUS REGISTER

| | | <u>,</u> | | | | | | · · | | | | | • |
|--|----------------------|----------------------------------|-----------------------------------|-------------------------------|-----------------------------------|---------------------------------------|---------------|------------------------|-------------------------------------|---|---------------|------------------------|-------------|
| F I G. 26B SERIAL BUS REGISTER | FUNCTION | COUNTER FOR ISOCHRONOUS TRANSFER | REGISTER FOR TIME SYNCHRONIZATION | S. Iddi of Chile A. Ind Child | AEGIOLEA HELALING TO POWER SUPPLY | TO CONTROL RETRY IN TRANSACTION LAYER | RESERVATION # | NODE ID OF BUS MANAGER | TO MANAGE ISOCHRONOUS TRANSFER BAND | TO MANAGE CHANNEL NUMBER FOR ISOCHRONOUS TRANSFER | | HEGISTEH FOR DIAGNOSIS | RESERVATION |
| | REGISTER NAME | CYCLE_TIME | BUS_TIME | POWER_FAIL_IMMINENT | POWER_SOURCE | BUSY_TIMEOUT | | BUS_MANAGER_ID | BANDWIDTH_AVAILABLE | CHANNELS_AVAILABLE | MAINT_CONTROL | MAINT_UTILITY | |
| Totalis et Joseph | OFFSET (hexadecimal) | 200 | 204 | 208 | , 20C | 210 | 214~218 | 21C | 220 | 224~228 | 22C | 230 | 234~3FC |

FIG. 26C SERIAL-BUS NODE RESOURCE REGISTER

| • | | | | 7 | • • |
|----------------------|-------------|-------------------------------------|-------------|---|-------------|
| FUNCTION | RESERVATION | INFORMATION ON SERIAL BUS STRUCTURE | RESERVATION | INFORMATION ON TRANSFER SPEED OF SERIAL BUS | RESERVATION |
| REGISTER NAME | | TOPOLOGY-MAP | · | SPEED-MAP | |
| OFFSET (hexadecimal) | 800~FFC | 1000~13FC | 1400~1FFC | 2000~2FFC | 3000~FFFC |

FIG. 26D

MINIMUM FORMAT CONFIGURATION ROM

| VENDOR ID | |
|-----------|--|
| 01 | |


FIG. 26E

GENERAL FORMAT CONFIGURATION ROM

| | NOT ASTER, | | | | |
|--------------------------|--|---|---|--------------------|------------------------------|
| CRC | I ON WHETHER OR AGEMENT, CYCLE N | E FUNCTION) | SOFT VERSION) | | |
| LENGTH OF ROM | AND INFORMATION RESOURCE MANA | root_directory (INDICATE VENDOR ID AND NODE FUNCTION) | unit_directories (INDICATE UNIT TYPE AND DRIVER SOFT VERSION) | root & unit_leaves | vendor_dependent_information |
| _ | DE OF 1394 BUS / ISOCHRONOUS | ry (INDICATE VEI | (INDICATE UNIT | root & ur | vendor_depend |
| LENGTH OF bus_info_block | bus_info_block (ASCII CODE OF 1394 BUS AND INFORMATION ON WHETHER OR NOT NODE HAS CAPABILITIES OF ISOCHRONOUS RESOURCE MANAGEMENT, CYCLE MASTER, AND BUS MANAGEMENT) | root_director | unit_directories | | |
| LENG | bus NOD AND | | | | \; |

, ·


FIG. 27A




56

FIG. 27B


U.C. Fld.





0.1-.1

F1G. 28B



\$





FIG. 30



F1G. 31

AV/C COMMAND FRAME

TRANSMITTED FIRST

| | ctype subunit_type subunit | opcode | operand [0] |
|-------------|------------------------------------|------------------|-------------|
| operand [1] | operand [2] | operand [3] | operand [4] |
| | : | | |
| operand [n] | Zero | pad bytes (if ne | cessary) |


TRANSMITTED LAST

:1G. 32

AV/C RESPONSE FRAME

| 0000 | response | response subunit_type subunit | epoodo | operand [0] |
|-------|-------------|-------------------------------|-------------------------------|----------------------------|
| opera | operand [1] | operand [2] | operand [3] | operand [4] |
| | | - : | | |
| opera | operand [n] | Jez | zero pad bytes (if necessary) | essarv) |
| | | | , | - - - - - - |

TRANSMITTED LAST



G. Alli.






FIG. 35





aven, il. G. Fiffi.

ILAUS (III)

FIG. 37




FIG. 38




FIG. 39





FIG. 40



AM.


FIG. 41

| COMMAND CLASSIFICATION | COMMAND | RESPONSE | |
|---------------------------|----------------|------------------------|---|
| STATUS | GetStatus | GetStatusResponse | |
| CONTROL | PrintReset | Print ResetResponse | - |
| | PrintStart | PrintStartResponse | _ |
| | PrintStop | PrintStopResponse | |
| | InsertPaper | SInsertPaperResponse | |
| | EjectPaper | EjectPaperResponse | |
| | CopyStart | CopyStartResponse | |
| | CopyEnd | CopyEndResponse | |
| BLOCK / BUFFER | BlockSize | BlockSizeResponse | |
| | BlockAddress | BlockAddressResponse | |
| | FreeBlock | FreeBlockResponse | |
| | WriteBlocks | WriteBlocksResponse | |
| | BufferConfig | BufferConfigResponse | |
| | SetBuffer | SetBufferResponse | |
| CHANNEL | OpenChannel | OpenChannelResponse | |
| | CloseChannel | CloseChannelResponse | |
| TRANSFER | TransferMethod | TransferMethodResponse | |
| FORMAT | SetFormat | SetFormatResponse | |
| LOG-IN | Login | LoginResponse | |
| | Logout | LogoutResponse | |
| | Reconnect | ReconnectResponse | _ |
| DATA | WriteBlock | | _ |
| | WriteBuffer | · · | _ |
| | PullBuffer | | |

FIG. 42

| EXIF(TIFF, JPEG) | EXIF NON-COMPRESSED AND COMPRESSED DATA |
|------------------|---|
| TIFF/EP | TIFF EXTENDED VERSION |
| RGB | RGB RAW IMAGE |
| YUV | YUV RAW IMAGE |
| YCrCb · | YCrCb RAW IMAGE |
| СМҮК | CMYK RAW IMAGE |
| Vendor Specific | VENDOR DEFINITION |








FIG. 46




FIG. 47






FIG. 48







DEVICE




FIG. 52




FIG. 53








FIG. 54









F.I.G. 58






FIG. 59








FIG. 62




FIG. 63

